

UAE

Email: mathews@generaltechuae.com

Tel: +971 (0) 2 550 7702 Fax: +971 (0) 2 550 7706 SAUDI

Mathews@generaltechsaudi.com

Tel: +966 (0) 3 834 4264 Fax: +966 3 834 4538

Mitutoyo 129-131 Depth Micrometer, Interchangeable Rods 0-4", 4"

This interchangeable rod type micrometer can be used for wide range measurements. It offers you the following benefits:

- ø4mm interchangeable rods, with lapped measuring surfaces, enable you to make wide-range measurement
- The ratchet stop provides constant measuring force.
- Measuring rod lock.

Specifications	Details
Flatness of reference surface (base)	1.3 µm for 63.5 mm
Micrometer Head Feed (0-25 mm)	±3 Âμm
Zero point errors of rods	±4 µm (0-150 mm)
Flatness of measuring face (rod)	0.3 µm
Spindle pitch	0.5 mm, with spindle lock
Measuring span	25 mm
Number of rods	4
Inch-Metric	Inch
Delivered	Including box and key
Scale	Thimble and sleeve satin chrome finish $\tilde{A} \lrcorner 18 \ mm$
Base	Hardened tool steel
Graduation	0.001
Measuring surfaces	Hardened, precision ground, micro-lap finish
Mass (main unit)	355 g

E-Mail:gentech@eim.ae P.O Box 25898 Sharjah Phone: 06-5436933/06-5436733 Website: www.generaltech.ae **United Arab Emirates** Fax : 06-5437077