



Dial Indicators

SERIES 2 — Standard Type, Inch Reading

Optional Accessories

- : Backs (See page F-33.)
- : Contact points (See page F-34.)



2416S



2803S-10

SPECIFICATIONS

Inch		Stem 3/8" dia. #4-48 UNF Thread						ANSI/AGD type				
Graduation	Range	Range /Rev	Dial Reading	Order No.		Accuracy		Measuring force				
				w/lug	Flat-back	First 2.5 Rev	Overall					
.0001"	.025"	.01"	0-10	2802S-10	2802SB-10	±.0001"	±.0001"	2.5N or less	✓			✓
.0001"	.025"	.01"	0-5-0	2803S-10	2803SB-10	±.0001"	±.0001"	2.5N or less	✓			✓
.0001"	.05"	.01"	0-10	2804S-10	2804SB-10	±.0001"	±.0002"	2.0N or less	✓			✓
.0001"	.05"	.01"	0-5-0	2805S-10	2805SB-10	±.0001"	±.0002"	2.0N or less	✓			✓
.0001"	.05"	.01"	10-0	2905S-10	2905SB-10	±.0001"	±.0002"	2.0N or less	✓	✓		✓
.0001"	.05"	.01"	0-5-0	2923S-10	2923SB-10	±.0001"	±.0002"	2.0N or less	✓	✓		✓
.0001"	.25"	.01"	0-10	2356S-10	2356SB-10	±.0001"	±.0005"	2.0N or less				✓
.0001"	.5"	.01"	0-10	2358S-10	2358SB-10	±.0001"	±.0008"	2.0N or less				✓
.0005"	.125"	.05"	0-50	2506S	2506SB	±.0005"	±.0005"	1.8N or less				
.0005"	.125"	.05"	0-25-0	2507S	2507SB	±.0005"	±.0005"	1.8N or less				
.0005"	.125"	.05"	0-25-0	2922S	2922SB	±.0005"	±.0005"	1.8N or less		✓		
.0005"	.5"	.05"	0-50	2514S	2514SB	±.0005"	±.0015"	1.8N or less				
.0005"	1"	.05"	0-50	2776S	2776SB	±.0005"	±.002"	2.5N or less				
.001"	.5"	.1"	0-100	2414S	2414SB	±.001"	±.001"	1.8N or less				
.001"	.5"	.1"	100-0	2914S	2914SB	±.001"	±.001"	0.4-1.8N		✓		
.001"	.5"	.1"	0-50-0	2415S	2415SB	±.001"	±.001"	1.8N or less				
.001"	1"	.1"	0-100	2416S	2416SB	±.001"	±.002"	1.8N or less				
.001"	1"	.1"	0-100	2416S-06*	2416SB-06*	±.001"	±.002"	1.8N or less				
.001"	1"	.1"	0-100	2416S-10	2416SB-10	±.001"	±.002"	1.8N or less				✓
.001"	1"	.1"	0-50-0	2417S	2417SB	±.001"	±.002"	1.8N or less				
.001"	1"	.1"	100-0	2904S	2904SB	±.001"	±.002"	1.8N or less		✓		
.001"	2"	1"	0-100	2424S-19	2424SB-19	±.001"	±.003"	2.5N or less	✓			✓

* Black Face



Shockproof type



Reverse reading type



Jeweled bearing type